

PRM-UST Music source, USB, SD, Tuner PLENA solutions



- MP3 playback from SD card and USB inputs
- FM tuner with RDS, presets and digital control
- Simultaneous operation of SD/USB player and FM tuner
- Separate outputs for digital source and FM tuner

The PRM-UST is a professional multi-source music player intended to be used as background music source for public address and commercial audio applications. It has USB interface, SD card input for playing stored music files, and tuner for FM frequency band broadcast receiver. It is used in hotels, shops, supermarkets, restaurants, bars, canteens, gyms, showrooms, and other places where background music creates the right atmosphere.

Functions

USB/SD

With an SD/USB memory capacity of up to 32 GB (up to 8000 tracks) and the option to connect the USB either on the front or rear panel, the digital player provides hours of high-quality, uninterrupted music playback from a single source. It supports music organized on a SD card or USB device in multiple folders. The player will automatically search and play all supported files on a flash memory device. It can play MP3 files with bit-rates from 32 kbps to 320 kbps, mono / stereo, and both constant bit-rates (CBR) and variable bit-rate (VBR) are supported.

Tuner

The digitally controlled FM tuner can accurately capture the radio stations and has presets memory to store favorite radio stations.

Outputs

The media player (SD or USB) and the tuner can operate simultaneously on different outputs. The level of the outputs can be set with the volume control buttons on the front panel or the remote. There is a combined output which has priority for media player, it automatically switches over to the FM tuner when there is no active media player input.

Regulatory information		
Safety	EN 62368-1	
Immunity	EN 55035	
Emissions	EN 55032 EN 61000-3-3	
Environment	EN IEC 63000	

Region	Regulatory compliance/quality marks	
Europe	CE	
Environment	RoHS	

Parts included

Quantity	Component
1	Music source PRM-UST
1	Mains power cord
1	Set of 19 inches mounting brackets with screws
1	Remote control (battery not included)

Quantity	Component
2	Stereo RCA audio cable
1	Antenna cord including connector
1	SD memory card (16 GB)
1	Quick installation guide
1	Safety information

Technical specifications

Electrical

Mains power supply			
Voltage range	110-120 VAC +/-10%, 50-60 Hz 220-240 VAC +/-10%, 50-60 Hz		
Power supply fuse	0.63 A / 250 V		
Power consumption (W)	15 W		
FM Tuner			
FM frequency range	87.5-108 MHz		
Frequency response	50 Hz—12 kHz +/-3 dB		
Channel separation (1 kHz)	>25 dB		
Signal-to-noise ratio	>50 dB		
FM input sensitivity	26 dBu		
Antenna impedance	75 ohm		
Audio output level	1.5 V rms +/-1 dB @10 kΩ		
USB or SD source			
Frequency response (Hz)	50 Hz—18 kHz +/-1 dB		
Signal-to-noise ratio (1kHz)	>75 dB		
Total harmonic distortion (1 kHz)	<0.5%		
Channel separation (1 kHz)	>70 dB		
Audio output level	1.5 V rms +/-1 dB at 10 k Ω		

Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 www.boschsecurity.com/xc/en/contact/ www.boschsecurity.com

Germany: Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Tel.: +49 (0)89 6290 0 Fax:+49 (0)89 6290 1020 de.securitysystems@bosch.com www.boschsecurity.com

ports together) Memory card capacity (GB) 32 GB maximum Supported file structure FAT. FAT32 and exFAT Supported audio files mp3, wma, wav, flac, ape, m4a Mechanical Dimension (H x W x D) (mm) (with 44 mm x 482 mm x 250 mm brackets) Dimension $(H \times W \times D)$ (in) (with 1.73 in x 18.98 in x 9.84 in brackets) Dimensions (H x W x D) (mm) 44 mm x 430 mm x 250 mm (without brackets) Dimensions (H x W x D) (in) (without 1.73 in. x 16.93 in x 9.84 in. brackets) Mounting Stand-alone, 19" rack (19" wide, 1 U high) Color in RAL RAL 9017 Traffic black Weight (kg) (unit) 3.20 kg Remote control dimensions 130 mm x 44 mm x 20 mm (L x W x D) (mm) (remote control) Weight (g) (remote control without 32 g batteries)

Environmental

USB output current limit

Operating temperature (°C)	0 °C – 45 °C
Storage temperature (°C)	-40 °C – 70 °C
Operating relative humidity, non- condensing (%)	<90%

Ordering information

PRM-UST Music source, USB, SD, Tuner USB/SD MP3 player with FM tuner functions. Order number PRM-UST | F.01U.397.942

North America:

Norm America: Bosch Security Systems, LLC 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.com

Asia-Pacific:

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 www.boschsecurity.com/xc/en/contact/ www.boschsecurity.com

Data subject to change without notice | 202206291035 | V9 | June 29, 2022

500 mA max. (front and rear USB